


# Filtering theory: Battling Aliasing with Antialiasing

Tomas Akenine-Möller  
Department of Computer Engineering  
Chalmers University of Technology

# What is aliasing?




# Why care at all?



- Quality!!
- Example: Final fantasy
  - The movie against the game
  - In a broad way, and for most of the scenes, the only difference is in the number of samples and the quality of filtering


# Computer graphics is a SAMPLING & FILTERING process!

- Pixels




Demo


- Texture



- Time




# Sampling and reconstruction



- Sampling: from continuous signal to discrete
- Reconstruction recovers the original signal
- Care must be taken to avoid aliasing
- Nyquist theorem: *the sampling frequency should be at least 2 times the max frequency in the signal*
- Often impossible to know max frequency (bandlimited signal), or the max frequency is often infinite...


# Sampling theorem

- Nyquist theorem: *the sampling frequency should be at least 2 times the max frequency in the signal*




# Sampling is simple, now turn to: Reconstruction

- Assume we have a bandlimited signal (e.g., a texture)
- Use filters for reconstruction




# Reconstruction with box filter (nearest neighbor)







# Reconstruction with tent filter



Nearest neighbor


Linear



32x32  
texture

$$\text{sinc}(x) \equiv \begin{cases} 1 & \text{for } x = 0 \\ \frac{\sin x}{x} & \text{otherwise,} \end{cases}$$

# Reconstruction with sinc filter





- In theory, the ideal filter
- Not practical (infinite extension, negative)

# Resampling

Enlarging or diminishing signals


- Enlarging easy: just use filter (e.g. box or tent) to compute intermediate values.
- For minification, one way is to take the average of the corresponding samples

Nearest neighbor





32x32  
texture

# Screen-based Antialiasing





- Hard case: edge has infinite frequency
- Supersampling: use more than one sample per pixel



# Formula and... examples of different schemes


$$p(x, y) = \sum_{i=1}^n w_i c(i, x, y)$$

- $w_i$  are the weights in  $[0, 1]$
- $c(i, x, y)$  is the color of sample  $i$  inside pixel




# Jittered sampling

- Regular sampling cannot eliminate aliasing – only reduce it!
- Why?
- Because edges represent infinite frequency
- Jittering replaces aliasing with noise
- Example:



# Moire example



Moire patterns



Noise + gaussian blur

(no moire patterns)

Modified by Ulf Assarsson, 2004


# Patterns

- Texture zoomed out until square  $< 1$  pixel






# SSAA, MSAA and CSAA



- Super Sampling Anti Aliasing
  - Stores duplicate information (color, depth, stencil) for each sample and fragment shader is run for each sample.
  - Corresponds to rendering to an oversized buffer and downfiltering.
- Multi Sampling Anti Aliasing
  - Shares some information between samples. E.g:
    - Fragment shader only run once per fragment.
    - Stores a color per sample and typically also a stencil and depth-value per sample
- Coverage Sampling Anti Aliasing
  - Once per fragment:
    - Depth-value and executing the fragment shader
  - A coverage mask per pixel:
  - Each sample holds a 2-bit index into a storage of up to four colors per pixel

16x CSAA




# The A-buffer Multisampling technique

- Takes  $>1$  samples per pixel, and shares computations between samples inside a pixel
- Supersampling does not share computations (depth, fragment shading)
- Examples:
  - Lighting may be computed once per pixel
  - Texturing may be computed once per pixel
- Strength: aliasing edges (and properly handling transparency)

# The A-buffer



- To deal better with edges: use a coverage mask per pixel
- Coverage mask, depth, & color make up a fragment
- During rendering fragments are discarded when possible (depth test)
- When all polygons have been rendered, the fragments are merged into a visible color
  - Allows for sorting transparent surfaces as well
  - But costs memory



# Another multisampling technique

## Quincunx


Quincunx




- Generate 2 samples per pixel at the same time
- $w_1=0.5$ ,  $w_2=0.125$ ,  $w_3=0.125$ ,  $w_4=0.125$ ,  $w_5=0.125$  (2D tent filter)
- All samples gives the same effect on the image (mid pixel = 0.5, corner pixels =  $4*0.125=0.5$ )
- Was available on NVIDIA GeForce3 and up

# Yet another scheme: FLIPQUAD multisampling


- Recap, RGSS:
  - One sample per row and column
- Combine good stuff from RGSS and Quincunx





[Demo](#)



- Weights: 0.25 per sample
- Performs better than Quincunx



# ATI Radeon 2900



From [www.pcper.com](http://www.pcper.com)

- Examples of 2 filter modes

# More on filtering theory and practice

- Especially important for texturing and filtering of textures
- More about this in next lecture

**THE END**

Hand in your  
Muddy Cards