

15 Streams and files


```
import java.io.*;
```

Overview

- Binary data vs textual data
- Simple file processing - examples
- The stream model
- Bytes and characters
- Buffering
- Byte streams
- Character streams
- Binary streams
- Direct access files


Binary data vs text

- Internally, all data is stored in binary format during program execution.
- *Text is more readable to humans than bits!*



Binary data vs text

- ... but bits are more readable to computers than text.
- No need for expensive translations.
- Binary files use less space than text files.



input-output

- The `java.io` package supports input-output.
- Input-output is particularly error-prone.
 - It involves interaction with the external environment.
- `java.io.IOException` is a checked exception.

Readers, writers, byte streams

- Readers and writers deal with textual input and output.
 - Based around the `char` type.
- Byte streams deal with binary data.
 - Based around the `byte` type.
- The `address-book-io` project illustrates textual IO.

Text output to file

- Use the `FileWriter` class.
 - Open a file.
 - Write to the file.
 - Close the file.
- Failure at any point results in an `IOException`.

Text output to file

```
try {  
    FileWriter writer =  
        new FileWriter("name of file");  
    while(there is more text to write) {  
        ...  
        writer.write(next piece of text);  
        ...  
    }  
    writer.close();  
}  
catch(IOException e) {  
    something went wrong when accessing the file  
}
```

Text input from a file

- Use the `FileReader` class.
- Augment with `BufferedReader` for line-based input.
 - Open a file.
 - Read from the file.
 - Close the file.
- Failure at any point results in an `IOException`.

Text input from the keyboard

- `System.in` maps to the keyboard.
 - `java.io.InputStream`
- Often wrapped in a `java.util.Scanner`:
 - `new Scanner(System.in);`
- `Scanner` supports *parsing* of textual input.
 - `nextInt`, `nextLine`, etc.
- `Scanner` with `File` an alternative to `BufferedReader` with `FileReader`.
 - `new Scanner(new File("filename"));`

Text input from a file using a `FileReader`

```
try {  
    BufferedReader reader =  
        new BufferedReader(  
            new FileReader("filename"));  
    String line = reader.readLine();  
    while(line != null) {  
        do something with line  
        line = reader.readLine();  
    }  
    reader.close();  
}  
catch(FileNotFoundException e) {  
    the specified file could not be found  
}  
catch(IOException e) {  
    something went wrong with reading or closing  
}
```

Text input from the keyboard using a `Scanner`

```
try {  
    Scanner in = new Scanner(System.in);  
  
    while(in.hasNextLine()) {  
        String line = in.nextLine();  
        do something with line  
    }  
}  
catch(FileNotFoundException e) {  
    the specified file could not be found  
}  
catch(IOException e) {  
    something went wrong with reading or closing  
}
```

The stream i/o model

- Isolates programming from low level environment details
 - Streams add an abstract layer smoothing out the differences between various sources (or targets) for i/o operations.
- Streams can connect to external files, communication sockets, internal data structures like arrays and strings, etc

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 13

Bytes and characters

- **Byte**
 - 8 bit signed integer [-128,127]
- **Character**
 - Java uses **Unicode 16 bit character** *internally* in programs.
- Common *external* character formats:
 - Unicode 16 bit character
 - ASCII 8 bit
 - UTF-8 variable length
 - "UTF8"
 - **LATIN_1**
 - "8859_1"
 - MS-DOS (Swedish)
 - "Cp850"

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 14

Buffering

- A large number of single byte or character i/o operations is inefficient.
- By using *buffering* larger chunks of data can be treated in fewer i/o operations
 - thus faster performance.
- Java uses *buffered streams* to implement buffered i/o.

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 15

Wrapper classes

- Many classes in **java.io** act as *wrapper classes* (the *decorator* design pattern).
- Ex.




```

PrintWriter out =
    new PrintWriter(
        new BufferedWriter(
            new FileWriter("output file name")));
    
```

Lecture 15 16


Byte input stream data flow



Object oriented programming, DAT042, D2, 12/13, lp 1







Lecture 15 17

Character input stream data flow




Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 18



Objektorienterad programmering D2, förel. 15


Byte output stream class relations



Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 25

Character output stream class relations



Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 26

Byte input stream operations

abstract class InputStream

```

int      read()
int      read(byte[] b)
int      read(byte[] b,int offset,int length)
long     skip(long n)
int      available()
boolean  marksupported()
void     mark(int limit)
void     reset()
void     close()
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 27

Byte output stream operations

abstract class OutputStream

```

void write(int b)
void write(byte[] b)
void write(byte[] b,int offset,int length)
void flush()
void close()
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 28

Character input stream operations

abstract class Reader

```

int      read()
int      read(char[] b)
int      read(char[] b,int offset,int length)
long     skip(long n)
boolean  ready()
boolean  marksupported()
void     mark(int limit)
void     reset()
void     close()
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 29

Character output stream operations

abstract class Writer

```


void write(int c)
void write(char[] b)
void write(char[] b,int offset,int length)
void write(String str)
void write(String str,int offset,int length)
void flush()
void close()
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 30

Ex. Text to binary conversion

- Read a text file containing long digit strings and write the corresponding numbers to a binary file. Explore the [text_to_binary project](#).



Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 31

Ex. Text to binary (2)

```
BufferedReader in =  
    new BufferedReader(  
        new FileReader("text infile name"));  
OutputStream out =  
    new BufferedOutputStream(  
        new FileOutputStream("binary outfile name"));  
...  
inputLine = in.readLine();  
if ( inputLine == null )  
    // done  
    BigInteger i = new BigInteger(inputLine);  
    byte[] bytes = i.toByteArray();  
    out.write(bytes.length);  
    out.write(bytes,0,bytes.length);  
...  
}
```


A brace on the right side of the code indicates a loop from the first 'inputLine' assignment to the final 'out.write' statement.

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 32

Ex. Binary to text conversion

- Read a binary file containing large numbers in 2-complement binary form and write the corresponding digits to a text file. Explore the [binary_to_text project](#).



Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 33

Ex. Binary to text (2)

```
BufferedInputStream in =  
    new BufferedInputStream(  
        new FileInputStream("binary infile name"));  
PrintWriter out =  
    new PrintWriter(  
        new BufferedWriter(  
            new FileWriter("text outfile name")));  
...  
int noOfBytes = in.read();  
byte[] buf = new byte[noOfBytes];  
if ( in.read(buf,0,noOfBytes) == -1 )  
    // done  
    BigInteger i = new BigInteger(buf);  
    out.println(i);  
...
```

A brace on the right side of the code indicates a loop from the first 'noOfBytes' assignment to the final 'out.println' statement.

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 34


Binary streams

- Binary data are treated differently depending on their kind of data type.
- For built in types like int, char, float,... use [DataStreams](#)
- For object types, use [ObjectStreams](#)

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 35


Byte input stream class relations



Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 36

Byte output stream class relations



Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 37

DataInput operations

```

interface DataInput
boolean readBoolean()
byte   readByte()
char  readChar()
short readShort()
int   readInt()
long  readLong()
float readFloat()
double readDouble()
String readUTF()
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 38

DataInput operations (2)

```

interface DataInput (cont.)
int   readUnsignedByte()
int   readUnsignedShort()
void  readFully(byte[] b)
void  readFully(byte[] b,int off,int len)
void  skipBytes(int len)
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 39

DataOutput operations

```

interface DataOutput
void writeBoolean()
void writeChar()
void writeDouble()
void writeShort()
void writeInt()
void writeLong()
void writeFloat()
void writeDouble()
void writeUTF(String s)
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 40

DataOutput operations (2)

```

interface DataOutput (cont.)
void writeChars(String s)
void writeBytes(String s)
void write(int b)
void write(byte[] b)
void write(byte[] b,int off,int len)
int  size()
  
```

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 41

Ex. Array save/load operations

```

public class ArrayIo {
  public static void
  save(long[] array, String fileName)
  throws IOException
  { ... }

  public static long[]
  load(String fileName) throws IOException
  { ... }
}
  
```

Explore the *array_io* project.

Object oriented programming, DAT042, D2, 12/13, Ip 1

Lecture 15 42

Array save operation

```
public static void
save(long[] array, String fileName)
throws IOException
{
    DataOutputStream out =
        new DataOutputStream(
            new FileOutputStream(fileName));
    out.writeInt(array.length);
    for ( long element : array )
        out.writeLong(element);

    out.close();
}
```

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 43

Array load operation

```
public static long[]
load(String fileName)
throws IOException
{
    DataInputStream in =
        new DataInputStream(
            new FileInputStream(fileName));
    int size = in.readInt();
    long[] array = new long[size];
    for ( int i = 0; i < array.length; i++ )
        array[i] = in.readLong();

    in.close();
    return array;
}
```

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 44

Binary streams of object types

- Whole networks of inter-connected objects may be "flattened" and written to object streams
 - and later be read back into the program again.
- To state that an object can be flattened, its class must implement
interface Serializable
- Typical application: Saving the program state for later resumption, e.g. in computer games.
- More on this subject in a forthcoming lecture!*

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 45

Random access files

- A random access file consists of a sequence of *equally sized records*.
- A *file pointer* contains the current position for the next read/write operation.
- The file pointer is advanced after each read/write operation, but it may also be *manipulated explicitly* to direct i/o operations to particular records.

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 46

Random access files (2)


- All records must have *exactly the same size*.
- Record types solely based on the primitive data types can be handled without complications.
- If a record type contains *strings*, they have to be *padded* to make up for size differences.
- Typical application: A database file of updatable bank accounts.

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 47

Random access file type relations


- Random access files are *both* input files and output files at the same time!



Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 48

Random access file operations



Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 49

Random access file operations (2)

class RandomAccessFile	
<i>Object construction</i>	Mode is either "r" (read), or "wr" (read/write).
RandomAccessFile(name, mode)	
long getFilePointer()	Return the file pointer offset measured from the beginning of this file.
void seek(pos)	Set file pointer offset measured from the beginning of this file.
long length()	Return the file length measured in bytes.
void setLength(n)	Set the file length to n bytes.

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 50

The java.io.File class

- Objects of class **File** provide system-independent information about files and directory pathnames.
- Useful for directory traversal, file creation, renaming, ...

Object oriented programming, DAT042, D2, 12/13, lp 1

Lecture 15 51