

15 Streams and files

```
import java.io.*;
```

Overview


- Binary data vs textual data
- Simple file processing - examples
- The stream model
- Bytes and characters
- Buffering
- Byte streams
- Character streams
- Binary streams
- Direct access files

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 2

Binary data vs text

- Internally, all data is stored in binary format during program execution.
- *Text is more readable to humans than bits!*




Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 3

Binary data vs text

- *... but bits are more readable to computers than text.*
- *No need for expensive translations.*
- *Binary files use less space than text files.*



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 4

Text input-output

- The `java.io` package supports input-output.
- Input-output is particularly error-prone.
 - It involves interaction with the external environment.
- `java.io.IOException` is a checked exception.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 5

Readers, writers, byte streams

- Readers and writers deal with textual input and output.
 - Based around the `char` type.
- Byte streams deal with binary data.
 - Based around the `byte` type.
- The *address-book-io* project illustrates textual IO.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 6

Text output to file

- Use the `FileWriter` class.
 - Open a file.
 - Write to the file.
 - Close the file.
- Failure at any point results in an `IOException`.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 7

Text output to file

```
try {
    FileWriter writer =
        new FileWriter("name of file");
    while(there is more text to write) {
        ...
        writer.write(next piece of text);
        ...
    }
    writer.close();
}
catch(IOException e) {
    something went wrong when accessing the file
}
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 8

Text input from a file

- Use the `FileReader` class.
- Augment with `BufferedReader` for line-based input.
 - Open a file.
 - Read from the file.
 - Close the file.
- Failure at any point results in an `IOException`.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 9

Text input from the keyboard

- `System.in` maps to the keyboard.
 - `java.io.InputStream`
- Often wrapped in a `java.util.Scanner`:
 - `new Scanner(System.in);`
- `Scanner` supports *parsing* of textual input.
 - `nextInt`, `nextLine`, etc.
- `Scanner` with `File` an alternative to `BufferedReader` with `FileReader`.
 - `new Scanner(new File("filename"));`

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 10

Text input from a file using a FileReader

```
try {
    BufferedReader reader =
        new BufferedReader(
            new FileReader("filename"));
    String line = reader.readLine();
    while(line != null) {
        do something with line
        line = reader.readLine();
    }
    reader.close();
}
catch(FileNotFoundException e) {
    the specified file could not be found
}
catch(IOException e) {
    something went wrong with reading or closing
}
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 11

Text input from the keyboard using a Scanner

```
try {
    Scanner in = new Scanner(System.in);

    while(in.hasNextLine()) {
        String line = in.nextLine();
        do something with line
    }
}
catch(FileNotFoundException e) {
    the specified file could not be found
}
catch(IOException e) {
    something went wrong with reading or closing
}
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 12

The stream i/o model

- Isolates programming from low level environment details
 - Streams add an abstract layer smoothing out the differences between various sources (or targets) for i/o operations.
- Streams can connect to external files, communication sockets, internal data structures like arrays and strings, etc

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 13

Bytes and characters

- **Byte**
 - 8 bit unsigned integer
- **Character**
 - Java uses **Unicode 16 bit character** internally in programs.
- Common **external character formats**:
 - Unicode 16 bit character
 - ASCII 8 bit
 - UTF-8 variable length
 - "UTF8"
 - LATIN_1
 - "8859_1"
 - MS-DOS (Swedish)
 - "Cp850"

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 14

Buffering

- A large number of single byte or character i/o operations is inefficient.
- By using **buffering** larger chunks of data can be treated in fewer i/o operations
 - thus faster performance.
- Java uses **buffered streams** to implement buffered i/o.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 15

Wrapper classes

- Many classes in `java.io` act as **wrapper classes** (the **decorator** design pattern).
- Ex.




```

PrintWriter out =
    new PrintWriter(
        new BufferedWriter(
            new FileWriter("output file name")));
    
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 16


Byte input stream data flow



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 17


Character input stream data flow



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 18


Bridging from byte in-streams to character in-streams



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 19


Byte input stream class relations



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 20


Character input stream class relations



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 21


Byte Output stream data flow



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 22


Character output stream data flow



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 23


Bridging from character out-streams to byte out-streams




Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 24

Byte output stream class relations



Character output stream class relations



Byte input stream operations

```

abstract class InputStream
int    read ()
int    read (byte[] b)
int    read (byte[] b,int offset,int length)
long   skip (long n)
int    available ()
boolean markSupported ()
void   mark (int limit)
void   reset ()
void   close ()
    
```

Byte output stream operations

```

abstract class OutputStream
void write (int b)
void write (byte[] b)
void write (byte[] b,int offset,int length)
void flush ()
void close ()
    
```

Character input stream operations

```

abstract class Reader
int    read ()
int    read (char[] b)
int    read (char[] b,int offset,int length)
long   skip (long n)
boolean ready ()
boolean markSupported ()
void   mark (int limit)
void   reset ()
void   close ()
    
```


Character output stream operations

```

abstract class Writer
void write (int c)
void write (char[] b)
void write (char[] b,int offset,int length)
void write (String str)
void write (String str,int offset,int length)
void flush ()
void close ()
    
```

Ex. Text to binary conversion

- Read a text file containing long digit strings and write the corresponding numbers to a binary file. Explore the *text_to_binary* project.



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 31

Ex. Text to binary (2)


```
BufferedReader in =
    new BufferedReader(
        new FileReader("text infile name"));
OutputStream out =
    new BufferedOutputStream(
        new FileOutputStream("binary outfile name"));
...
inputLine = in.readLine();
if ( inputLine == null )
    // done
BigInteger i = new BigInteger(inputLine);
byte[] bytes = i.toByteArray();
out.write(bytes.length);
out.write(bytes,0,bytes.length);
...
} loop
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 32

Ex. Binary to text conversion

- Read a binary file containing large numbers in 2-complement binary form and write the corresponding digits to a text file. Explore the *binary_to_text* project.



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 33

Ex. Binary to text (2)

```
BufferedInputStream in =
    new BufferedInputStream(
        new FileInputStream("binary infile name"));
PrintWriter out =
    new PrintWriter(
        new BufferedWriter(
            new FileWriter("text outfile name")));
...
int noOfBytes = in.read();
byte[] buf = new byte[noOfBytes];
if ( in.read(buf,0,noOfBytes) == -1 )
    // done
BigInteger i = new BigInteger(buf);
out.println(i);
...
} loop
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 34


Binary streams

- Binary data are treated differently depending on their kind of data type.
- For built in types like int, char, float,... use *DataStreams*
- For object types, use *ObjectStreams*

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 35


Byte input stream class relations



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 36

Byte output stream class relations



DataInput operations

```

interface DataInput
boolean readBoolean()
byte readByte()
char readChar()
short readShort()
int readInt()
long readLong()
float readFloat()
double readDouble()
String readUTF()
    
```

DataInput operations (2)

```

interface DataInput (cont.)
int readUnsignedByte()
int readUnsignedShort()
void readFully(byte[] b)
void readFully(byte[] b,int off,int len)
void skipBytes(int len)
    
```

DataOutput operations

```

interface DataOutput
void writeBoolean()
void writeChar()
void writeDouble()
void writeShort()
void writeInt()
void writeLong()
void writeFloat()
void writeDouble()
void writeUTF(String s)
    
```

DataOutput operations (2)

```

interface DataOutput (cont.)
void writeChars(String s)
void writeBytes(String s)
void write(int b)
void write(byte[] b)
void write(byte[] b,int off,int len)
int size()
    
```

Ex. Array save/load operations

```

public class ArrayIo {
    public static void
    save(long[] array,String fileName)
    throws IOException
    { ... }

    public static long[]
    load(String fileName) throws IOException
    { ... }
}
    
```

Explore the *array_io* project.

Array save operation

```
public static void
save(long[] array, String fileName)
throws IOException
{
    DataOutputStream out =
        new DataOutputStream(
            new FileOutputStream(fileName));
    out.writeInt(array.length);
    for ( long element : array )
        out.writeLong(element);

    out.close();
}
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 43

Array load operation

```
public static long[]
load(String fileName)
throws IOException
{
    DataInputStream in =
        new DataInputStream(
            new FileInputStream(fileName));
    int size = in.readInt();
    long[] array = new long[size];
    for ( int i = 0; i < array.length; i++ )
        array[i] = in.readLong();

    in.close();
    return array;
}
```

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 44

Binary streams of object types

- Whole networks of inter-connected objects may be "flattened" and written to object streams
- and later be read back into the program again.
- To state that an object can be flattened, it's class must implement
`interface Serializable`
- Typical application: Saving the program state for later resumption, e.g. in computer games.
- *More on this subject in a forthcoming lecture!*

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 45

Random access files

- A random access file consists of a sequence of *equally sized records*.
- A *file pointer* contains the current position for the next read/write operation.
- The file pointer is advanced after each read/write operation, but it may also be *manipulated explicitly* to direct i/o-operations to particular records.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 46

Random access files (2)


- All records must have *exactly the same size*.
- Record types solely based on the primitive data types can be handled without complications.
- If a record type contains *strings*, they have to be *padded* to make up for size differences.
- Typical application: A database file of updatable bank accounts.

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 47

Random access file type relations


- Random access files are *both* input files and output files at the same time!



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 48

Random access file operations



Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 49

Random access file operations (2)

| class RandomAccessFile | |
|--|--|
| <i>Object construction</i> | Mode is either "r" (read), or "rw" (read/write). |
| <code>RandomAccessFile (name, mode)</code> | |
| <code>long getFilePointer ()</code> | Return the file pointer offset measured from the beginning of this file. |
| <code>void seek (pos)</code> | Set file pointer offset measured from the beginning of this file. |
| <code>long length ()</code> | Return the file length measured in bytes. |
| <code>void setLength (n)</code> | Set the file length to n bytes. |

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 50

The java.io.File class

- Objects of class `File` provide system-independent information about files and directory pathnames.
- Useful for directory traversal, file creation, renaming, ...

Object oriented programming, DAT042, D2, 11/12, lp 1

Lecture 15 51