

Erlang and message passing

What does $f(5)$ return?

$f(0) \rightarrow 0;$
 $f(N) \rightarrow N + f(N-1).$

1. 0
2. 5
3. 15
4. the factorial of 5

What does $f(5)$ return?

$f(0) \rightarrow 0;$
 $f(N) \rightarrow N + f(N-1).$

1. 0
2. 5
3. 15
4. the factorial of 5

What does `g([a,b,c,d,e,f,g])` return?

`g([])` -> `[]`;
`g([X])` -> `[X]`;
`g([X|Y|T])` -> `[X|g(T)]`.

1. `[]`
2. `[a]`
3. `[a,b,c,d,e,f,g]`
4. `[a,c,e,g]`

What does `g([a,b,c,d,e,f,g])` return?

`g([])` -> [];
`g([X])` -> [X];
`g([X|Y|T])` -> [X|g(T)].

1. []
2. [a]
3. [a,b,c,d,e,f,g]
4. [a,c,e,g]

What do `h({3,B})` and `h({4,_})` return?

`h({3,B}) -> B;`

`h({_,3}) -> 3;`

`h({_,_}) -> 4.`

1. 3 and 3
2. 3 and 4
3. 4 and 3
4. 4 and 4

What do `h({3,B})` and `h({4,3})` return?

`h({3,B}) -> B;`

`h({_,3}) -> 3;`

`h({_,_}) -> 4.`

1. 3 and 3
2. 3 and 4
3. 4 and 3
4. 4 and 4

What does `k([])` return?

```
k({_,_,_}) -> [3,3,3];
```

```
k(X) ->
```

```
case X of
```

```
{A,B} -> A + B;
```

```
_ -> 0
```

```
end.
```

1. 0
2. [3,3,3]
3. It throws an exception
4. {0,0}

What does `k([])` return?

```
k({_,_,_}) -> [3,3,3];
k(X) ->
  case X of
    {A,B} -> A + B;
    _        -> 0
  end.
```

1. 0
2. [3,3,3]
3. It throws an exception
4. {0,0}